



GALGO^{MR}

PRE-Q[®]



CS

[Combined Service]



REGIONAL



| código | inch | mm | /32 | mm |
|------------|-------|-----|-----|------|
| 50 CS 14 | 5 | 127 | 14 | 11.1 |
| 54 CS 14 | 5 4/8 | 140 | 14 | 11.1 |
| 60 CS 16 | 6 | 152 | 16 | 12.7 |
| 64 CS 16 | 6 4/8 | 165 | 16 | 12.7 |
| ▶ 70 CS 16 | 7 | 178 | 16 | 12.7 |
| ▶ 70 CS 20 | 7 | 178 | 20 | 16 |
| ▶ 75 CS 22 | 7 5/8 | 194 | 22 | 17.5 |
| ▶ 80 CS 22 | 8 | 203 | 22 | 17.5 |
| ▶ 82 CS 22 | 8 2/8 | 210 | 22 | 17.5 |
| ▶ 84 CS 22 | 8 4/8 | 216 | 22 | 17.5 |
| ▶ 93 CS 22 | 9 3/8 | 238 | 22 | 17.5 |

| | |
|--------------------|--|
| Tracción: | Alta |
| Velocidad: | Moderada |
| Hombro redondeado: | No |
| Ala: | No |
| Sentido de giro: | No |
| Tipo de camino: | Carreteras secundarias sinuosas y con pendientes. |
| Beneficios: | Disponible para usos múltiples en camionetas, vehículos comerciales y recreativos. Ideal para caminos mojados, con lodo y nieve. |
| Cualidades: | Diseño de bloques alineados. Hombro abierto para una mejor autolimpieza y enfriamiento al rodado. Diseño de paso variable reduce el nivel de ruido al rodar. |

Recomendado:

Eje:

Tipo de llanta:



www.galgo.com.mx

Medidas de llantas recomendadas

| | | | |
|----------|-------------|-------------|-------------|
| 10.00R20 | 12R22.5 | 235/85R16 | 275/80R22.5 |
| 10.00R22 | 12R24.5 | 245/70R19.5 | 275/80R24.5 |
| 10R22.5 | 13R22.5 | 245/75R17.5 | 275/80R24.5 |
| 11.00R20 | 225/70R19.5 | 255/70R22.5 | 295/75R22.5 |
| 11R22.5 | 225/75R16 | 255/80R22.5 | 305/70R22.5 |
| 11R24.5 | 235/75R17.5 | 275/70R22.5 | 315/80R22.5 |